

Handle With Ease



Call Now! +91 7023301222 sales1@ahujagroup.in www.stackeasy.in

- ☑ Quality product from Ahuja Group.
- ☑ German Technology by FLUC GmbH.
- ☑ Heavy duty for moving heavy loads.
- ☑ Unique design and features
- ☑ World class after sales support.



INDEX

| Sr. No. | Code | Product Name | Page |
|---------|----------------------------|-------------------------------------|------|
| No. | | | |
| 1 | SE/HHPT/25 Eco | Hand Pallet Truck | 1 |
| 2 | SE/HHPT/25 | Hand Pallet Truck | 1 |
| 3 | SE/HHPT/30 | Hand Pallet Truck | 1 |
| 4 | SE/HHPT/50 | Hand Pallet Truck | 1 |
| 5 | SE/SHAKTI25/1150mm X 540mm | Hand Pallet Truck | 2 |
| 6 | SE/EUROPE 26 | Hand Pallet Truck | 2 |
| 7 | SE/LPT/52 | Hand Pallet Truck , Low Profile | 2 |
| 8 | SE/SHAKTI 25 LH | Hand Pallet Truck , Low Profile | 3 |
| 9 | SE/GERMANY 26 | Hand Pallet Truck | 3 |
| 10 | SE/PRV 20 | Paper Roll Version Pallet Truck | 3 |
| 11 | SE/SHAKTI25/800mm X 540mm | Hand Pallet Truck | 4 |
| 12 | SE/RTPT12 | Rough Terrain Pallet Truck | 4 |
| 13 | SE/HL/SP 1008 | High Lift Pallet Truck Single Stage | 4 |
| 14 | SE/HL/DP 1008 | High Lift Pallet Truck Two Stage | 5 |
| 15 | SE/PT70/1220X610 | Lift Table Truck | 5 |
| 16 | SE/PT100/1016X510 | Lift Table Truck | 5 |
| 17 | SE/PT50/1600x810 | Lift Table Truck | 6 |
| 18 | SE/PT100/2035x750 | Lift Table Truck | 6 |
| 19 | SE/PT30 | Lift Table Truck | 6 |
| 20 | SE/PT15 | Lift Table Truck | 6 |
| 21 | SE/VV/1009 | Stacker Low Height | 6 |
| 22 | SE/VV/1012 | Stacker Low Height | 6 |
| 23 | SE/VV/1016 | Stacker Low Height | 6 |
| 24 | SE/RDH/35 | Rotary Drum Handling Stacker | 7 |
| 25 | SE/HS 1008 | Manual Stacker | 7 |
| 26 | SE/HS 1016 | Manual Stacker | 7 |
| 27 | SE/MS 1016 | Manual Stacker | 7 |
| 28 | SE/MS 1516 | Manual Stacker | 7 |
| 29 | SE/SES 1016 | Semi-Electric Stacker | 8 |
| 30 | SE/SES 1025 | Semi-Electric Stacker | 9 |
| 31 | SE/SES 1030 | Semi-Electric Stacker | 10 |
| 32 | SE/SES 1516 | Semi-Electric Stacker | 11 |
| 33 | SE/SES 1525 | Semi-Electric Stacker | 12 |
| 34 | SE/SES 1530 | Semi-Electric Stacker | 13 |





Hydraulic Hand Pallet Truck

SE/HHPT/ 25 Eco

| Capacity | 2500 kg |
|----------------|----------|
| Lifting height | 200 mm |
| Fork Length | 1150 mm |
| Fork Width | 550 mm |
| Self weight | 73-92 kg |

Features:

- $\ \ \, \square$ Top quality & competitive.
- ☑ Fastest moving product
- ☑ Enhances productivity
- ✓ Long service life

Hydraulic Hand Pallet Truck

| | SE/HHPT/30 |
|-----------------|------------|
| Capacity | 3000kg |
| Lowered height | 85mm |
| Fork Length | 1150mm |
| Fork Width | 550mm |
| Over All Length | 1534mm |
| Lifting Height | 190mm |

Features:

- ☑ External is very smooth & nice appearance.
- ☑ Maintenance-free design.
- oxdot Integral hydraulic pump, which prevents any leakage.
- ☐ High-strength alloy steel carefully crafted, results in increased loading capacity.
- oxdot Set the active safety valve to prevent overloading.





Hydraulic Hand Pallet Truck

SE/ HHPT/50

| Capacity | 5000 kg |
|----------------|---------|
| Fork Length | 1150 mm |
| Fork Width | 550 mm |
| Lifting Height | 190 mm |
| Weight | 140 kg |

- ☑ Top quality & competitive.
- ☑ Heavy duty for moving heavy load.



Hydraulic Hand Pallet Truck

SE/SHAKTI 25/ 800mm X 540mm

| , | |
|---------------------|------------|
| Capacity | 2500 kg |
| Min.fork height | 85 mm |
| Max.fork height | 200 mm |
| Steering wheel | Ф200x50 mm |
| Load roller Single | Ф80x93 mm |
| Load roller Tandem | Ф80x70 mm |
| Size of forkes | 160x50 mm |
| Width overall forks | 540 mm |
| Fork length | 800 mm |
| | |

Features:

- Specially designed to lift and transport the widest variety of loads in stores and warehouse.
- ☑ Strong, torsion-resistant steel construction.
- Load-in/lead-out rollers under the fork tips enable pallets to be entered any kind of pallet.
- No routine maintenance at all is needed on the hydraulic unit and bearings.
- Hydraulic seals made in Germany, which prolong the working time of hydraulic unit.
- ☑ With different options for fork width and length.
- ☑ With options for Nylon, Rubber wheel and PU wheels.
- ✓ Parking brake optional.



Hydraulic Hand Pallet Truck

SE/SHAKTI 25 / 1150mm X540mm

- Specially designed to lift and transport the widest variety of loads in stores and warehouse.
- ☑ Strong, torsion-resistant steel construction.
- Load-in/lead-out rollers under the fork tips enable pallets to be entered any kind of pallet.
- No routine maintenance at all is needed on the hydraulic unit and bearings.
- Hydraulic seals made in Germany, which prolong the working time of hydraulic unit.





Hydraulic Shop Crane

SE/SC/1000

| Lifting Capacity | 250-1000kg |
|------------------|-------------|
| Beam Length | 1160-1460mm |
| Beam Height | 0- 2350 mm |
| Beam Size | 1126-1650mm |
| Power Unit | 7 ton |
| Self Weight | 115 Kg |

Features:

- ☑ Two kinds of lowering systems release nut& lever.
- $\ensuremath{\square}$ Handle with plate protection for workers safety





Hydraulic Lift Table Truck

SE/PT70/ 1220x610

| Capacity | 700 kg |
|----------------------------------|-------------|
| Min.table height | 445 mm |
| Max.table height | 1500 mm |
| Dimension of table | 1220x610 mm |
| Caster wheel | Ф125x40 mm |
| Foot pedal cycles to max.height | ≤97 times |
| Net Weight | 195 kg |
| Height of handle from the ground | 1015 mm |

Features:

- $\ oxdot$ Two kinds of lowering systems release nut & lever.

Hydraulic Lift Table Truck SE/PT100 /1016x510

| 3L/F1100/1010X310 | |
|----------------------------------|----------------|
| Capacity | 1000 kg |
| Min. table height | 380 mm |
| Max. table height | 990 mm |
| The dimension of table | 1016x510x55 mm |
| Caster wheel | Φ127x50 mm |
| Foot pedal cycles to max.height | ≤82 mm |
| Net Weight | 140 mm |
| Height of handle from the ground | 980 mm |
| | |

- $\ensuremath{\square}$ Two kinds of lowering systems release nut& lever.
- $\ensuremath{\square}$ Handle with plate protection for workers safety







Hydraulic Lift Table Truck

| SE, | /PT50/1600x810 | SE/PT100/2035X750 |
|----------------------------------|----------------|-------------------|
| Capacity | 500 kg | 1000 kg |
| Min.table height | 290 mm | 360 mm |
| Max.table height | 915 mm | 1360 mm |
| Dimension of table | 1600x810 mm | 2035x750 mm |
| Caster wheel | 125*40 mm | F180x50/F80x40 mm |
| Foot pedal cycles to max.height | ≤55 times | ≤200 times |
| Net Weight | 154 kg | 198 kg |
| Height of handle from the ground | 975 mm | 1000 mm |

Features:

- ☑ Two kinds of lowering systems release nut & lever.
- $\ oxdot$ Handle with plate protection, for workers safety.

Hydraulic Lift Table Truck

| | SE/PT 30 | SE/PT 15 |
|----------------------------------|------------|---------------|
| Capacity | 300 kg | 150 kg |
| Min.table height | 285/340 mm | 220 mm |
| Max.table height | 880 mm | 720 mm |
| The dimension of table | 850x500 mm | 700x450x36 mm |
| Caster wheel | Ф125x40 mm | Ф100x25 mm |
| Foot pedal cycles to max.height | ≤27 | ≤28 |
| Net Weight | 77 kg | 46 kg |
| Height of handle from the ground | 990 mm | 950 mm |

Features:

- $\ensuremath{\,\boxtimes\,}$ Two kinds of lowering systems release nut & lever.
- $\ensuremath{\square}$ Handle with plate protection for workers safety.





Hydraulic Stacker Low Height

| | SE/VV 1009 | SE/VV 1012 | SE/VV 1016 |
|---------------------|------------|-------------|-------------|
| Capacity | 1000 kg | 1000 kg | 1000 kg |
| Max. Fork Height | 900mm | 1200 mm | 1600 mm |
| Min. Fork Height | 86± 2mm | 86± 2 mm | 86± 2 mm |
| Fork Length | 1170mm | 1170 mm | 1170 mm |
| Size of fork | 150mm×50mm | 150 mm×50mm | 150 mm×50mm |
| Fork Width(outside) | 540mm | 540 mm | 540 mm |
| Fork Width(inside) | 240mm | 240 mm | 240 mm |
| Over Height | 1220mm | 1520 mm | 1920 mm |
| Over Width | 700mm | 700 mm | 700 mm |
| | | | |

- $\ oxdot$ Stacker is made of high quality steel.
- $\ oxdot$ Designed for durabulity, reliability and ease of use.
- $\ensuremath{\square}$ For low height application like inside the container.



Hydraulic Rotary Drum Handling Stacker SE/RDH 35

| - | |
|----------------|---------|
| Rated Capacity | 350 Kg |
| Lifting Height | 1425 mm |
| Overall Length | 1190 mm |
| Overall Width | 890 mm |
| Overall Height | 2020 mm |
| Net Weight | 155 Kg |

Features:

- ☑ Ideal for applications where barrels are stacked, transported or are being used for pouring the fluid inside.
- ☑ The rotation of the barrel is controlled by turning the control handle.





Ajustable Manual Stacker

| | SE/AMS/1016 | SE/AMS/2016 |
|-----------------------------|-----------------|-----------------|
| Capacity | 1000 Kg | 2000 Kg |
| Fork Length | 900 mm | 900 mm |
| Adjustable fork Width up to | 680mm | 680mm |
| Lower Fork Height | 85 mm | 85 mm |
| Lifting Height | 1600 mm | 1600 mm |
| Lifting speed (mm/stroke) | 20 | 20 |
| Dimension | 2100x750x1420mm | 2100x750x1420mm |
| Self Weight | 227kg | 250kg |
| | | |

Features:

- ☑ The newest design of hydraulic stacker.
- $\ oxdot$ Special C type mast which is more stable and strong.
- \square Quick lift pump to save time and labor.
- ☑ Easy-to-operate controller.

Hydraulic Manual Stacker

| | SE/MS 1016 | SE/MS 1516 |
|----------------|-------------------|-------------------|
| Capacity | 1000 kg | 1500 Kg |
| Fork Length | 1150 mm | 1150 mm |
| Fork Width | 550 mm | 550mm |
| Overall Length | 1280 mm | 1280mm |
| Load Center | 500 mm | 500mm |
| Lifting Height | 1600 mm | 1600mm |
| Net Weight | 250 kg | 250kg |

- ☑ High quality mast steel ensures rigidity, durability.
- ☑ Integral pump, which prevents loosening and is leak-proof.
- $\ensuremath{\square}$ High efficiency pump makes operating lighter &comfortable.
- $\ \ \, \square$ You can set the active safety valve to prevent overloading of use.
- ☑ Maintenance-free design, ensures security, reduces service cost.
- $\ensuremath{\square}$ Regardless of loading weight, lifting speed always remains the same.
- \square Handle and foot pedal operated.
- oxdot Hand control valve for precise control and convenience.







Skates

| | SE/S/NW/6000 | SE/S/NW/15000 |
|-------------------|----------------|----------------|
| Capacity | 6000 Kg | 15000 Kg |
| Dimension (LxBxH) | 300x222x110mm | 400x308x110mm |
| No of wheel | 4 Nos | 9 Nos |
| Wheel Size | 80x 70mm | 80x 70mm |
| Wheel Material | PU With handle | PU With handle |
| Self Weight | 16 Kg | 37 Kg |

Features:

- $\ oxdot$ Handle with plate protection, for workers safety.

Chip Collecting Trolley

| Capacity | 200 Kg |
|-----------|-------------|
| Material | Mild Steel |
| Condition | New |
| Cart Size | 600*900*900 |
| Color | Smoke gray |
| | |



Features:

- ☑ Trolley is fitted with 4 x 4 inchs
- oxdot wheels (2 x Swivel and 2 x Fix) Coolant Drain Valve



DRUM/STD/4WHLTRLY

| Capacity | 300 Kg |
|----------------|----------------------------|
| Dimension | 1440MMx700MMx900MM |
| Wheel Size | 250 x 60 mm |
| Wheel Material | Cushion Tyred Rubber Wheel |
| | |

- $\ensuremath{\square}$ To move the Drums manually from one place to another in the
- $\ensuremath{\square}$ plant , very easy smooth working



Hydraulic Semi-electric Stacker SE/SES1016

| 32/3231010 | |
|---|------------------|
| Drive | Manual |
| Type of operation | Pedestrian |
| Load Capacity /rated load | 1000 (Kg) |
| Load center distance | 800 (mm) |
| Wheelbase | 1210 (mm) |
| Weight(including battery) | 350Kg |
| Tyres | PU |
| Tyre size, front | 180x50mm |
| Tyre size, rear | 74x70mm |
| Wheels, number front/rear | 2/4 |
| Track width, front | 680 (mm) |
| Track width, rear | 400/490 (mm) |
| Lowered mast height | 1980 (mm) |
| Lift height | 1600 (mm) |
| Extended mast height | 1980 (mm) |
| Height of handle min./max. | 790/1156 (mm) |
| Fork height lowered | 85 (mm) |
| Overall length | 1720/1570 (mm) |
| Length to face of forks | 610/670 (mm) |
| Overall width | 777 (mm) |
| Fork dimensions | 60/180/1100 (mm) |
| width over forks | 570 (mm) |
| Aisle width for pallets 1000x1200 crossways | 2232 (mm) |
| Aisle with for pallets 800x1200 lengthways | 2166 (mm) |
| Turning radius | 1400 (mm) |
| Lift speed, laden/unladen | 90/140mm/s |
| Lowering speed, laden/unladen | 120/100mm/s |
| Parking brake | Manual |
| Lift motor rating at S3 15% | 1.5kw |
| Battery voltage, nominal capacity K5 12/150 | V/Ah |
| Battery weight | 45Kg |
| Footuses | |



Features:

- $\ oxdot$ Strong, robust and classical design
- $\ oxdot$ Has an appealing look.
- ☑ The smooth outline makes it stand out from traditional stacker.
- $\ensuremath{\square}$ Made of high quality steel to ensure stability and strength.
- \square Durable and easily serviceable.
- $\ \ \, \square$ Easy to operate.
- ☑ Built-in charger.

We don't sell products, we create life long relationship with customers.

All our customers are assured of the best in class technology, international quality products and world class after sales support.





Hydraulic Semi-electric Stacker SE/SES1025

| NA===1 |
|------------------|
| Manual |
| Pedestrian |
| 1000 (Kg) |
| 800 (mm) |
| 1210 (mm) |
| 410 Kg |
| PU |
| 180x50 mm |
| 74x70 mm |
| 2/4 |
| 680 (mm) |
| 400/490 (mm) |
| 1830 (mm) |
| 2500 (mm) |
| 3070 (mm) |
| 790/1156 (mm) |
| 85 (mm) |
| 1720/1580 (mm) |
| 610/670 (mm) |
| 777 (mm) |
| 60/180/1100 (mm) |
| 570 (mm) |
| 2232 (mm) |
| 2166 (mm) |
| 1400 (mm) |
| 90/140 mm/s |
| 120/100 mm/s |
| Manual |
| 1.5 kw |
| 12/150 V/Ah |
| 45 Kg |
| |

Features:


- ☑ Strong, robust and classical design.
- \square Has an appealing look.
- $\ensuremath{\square}$ The smooth outline makes it stand out from traditional stacker.
- ☑ Made of high quality steel to ensure stability and strength.
- $\ oxdot$ Durable and easily serviceable.
- ☑ Easy to operate.
- ☑ Built-in charger.

Established in 1970, Ahuja Group endeavours to build tomorrow's enterprises, optimise business and enhance and to end cutomer experience. We deliver quality beyond compare to serve any cutomer, any channel at anytime. A team of passionate, innovative, committed young minds driven by an intuitive zeal serves our very purpose of seamless thinking and working together and outperforming competetion.



The Best in Material Handling Equipment













Mr. Lalit Ahuja (MD, Ahuja Corporation Pvt. Ltd.) with Mr. Ravi Sehgal, Chairman EEPC, India

AHUJA CORPORATION PVT. LTD.

A-185, RIICO Prahladpura Industrial Area, Near Shivdaspura, Tonk Road, Jaipur 302022 Rajasthan, INDIA | Ph.: +91 141 5168300, +91 98292 29943 sales@ahujagroup.in | www.ahujagroup.in